

BASE STATION COMPARISON

+ Value in Weigh Tech
Hodnota ve vážící technice

FREE SOFTWARE:
Configure all our devices with our Toolkit. View and log data with LOG100. Just plug and play!



T24-BSd	
Order codes:	
Module size (H x W x L):	11 x 20.5 x 58 mm
Wireless Range:	500 m
Power supply:	USB (4.875 to 5.125 Vdc)
Antenna:	Integral (part of board)
Radio frequency:	2.4 GHz
Transmit power:	10 mW
Interface:	USB
Operating temperature:	-20 °C to +55 °C
Storage temperature:	-40 °C to +85 °C
Environmental Protection:	IP50
Software & Configurations:	T24-Toolkit & T24-LOG100
USPs:	<ul style="list-style-type: none"> - Very portable - Ideal for use with laptops & tablets - Smallest and most economically priced base station in our range



T24-BSu	
Order codes:	
Module size (H x W x L):	20 x 35 x 76 mm
Wireless Range:	500 m
Power supply:	USB (4.875 to 5.125 Vdc)
Antenna:	Integral (part of board)
Radio frequency:	2.4 GHz
Transmit power:	10 mW
Interface:	USB
Operating temperature:	-20 °C to +55 °C
Storage temperature:	-40 °C to +85 °C
Environmental Protection:	IP50
Software & Configurations:	T24-Toolkit & T24-LOG100
USPs:	<ul style="list-style-type: none"> - Wall mounted or desktop use - Can be moved independently of a laptop to achieve better reception



T24-BSue	
Order codes:	
Module size (H x W x L):	34 x 62 x 80 mm
Wireless Range:	800 m
Power supply:	USB (4.875 to 5.125 Vdc)
Antenna:	T24-ANTA (inside enclosure)
Radio frequency:	2.4 GHz
Transmit power:	10 mW
Interface:	USB
Operating temperature:	-20 °C to +55 °C
Storage temperature:	-40 °C to +85 °C
Environmental Protection:	IP67 / Nema4 (95% non-condensing max humidity level)
Software & Configurations:	T24-Toolkit & T24-LOG100
USPs:	<ul style="list-style-type: none"> - Wall mounted or desktop use. - Can be moved independently of a laptop to achieve better reception - Improved IP rating & greater range



T24-BSi	
Order codes:	
Module size (H x W x L):	57 x 84 x 164 mm
Wireless Range:	800 m
Power supply:	USB or 9 to 32 Vdc (supply current at 12V: 100mA)
Antenna:	T24-ANTA (inside enclosure)
Radio frequency:	2.4 GHz
Transmit power:	10 mW
Interface:	USB / RS232 / RS485
Operating temperature:	-20 °C to +55 °C
Storage temperature:	-40 °C to +85 °C
Environmental Protection:	IP67 / Nema4 (95% non-condensing max humidity level)
Software & Configurations:	T24-Toolkit & T24-LOG100
USPs:	<ul style="list-style-type: none"> - Wall mounted or desktop use - Can be moved independently of a laptop to achieve better reception - Data collection for PC/PLC; Has USB/RS232/RS485 interface